

LIGHTBAR #26010-47

47" 12-24VDC AMBER / WHITE



FEATURES

- ✓ Operating voltage: DC 12-24V DC
- ✓ Dual colour and single colour operation
- ✓ 28 Flash Patterns for different use
- ✓ Stop Turn Tail
- ✓ Take Down and Alley Lights
- ✓ Traffic Director
- ✓ Vibration Resistant design
- ✓ Inner door frame brackets included
- ✓ Tough polycarbonate lens with UV resistant
- ✓ Super-narrow design is easy to install anywhere
- ✓ With memory function
- ✓ IP 66 rating
- ✓ Reverse polarity protection
- ✓ 30°C to +60°C operating temperature
- ✓ Controller included
- ✓ Aluminum base



Extruded aluminum base



**Polycarbonate
UV Protected**

Flash Patterns

#1	Single (ECE R65)	#11	Cycle	#21	CW - CCW Constant flash
#2	Double (ECE R65)	#12	Triple	#22	Left arrowstick
#3	Quad (ECE R65)	#13	Triple half to half	#23	Right arrowstick
#4	Octa	#14	One - One Single	#24	Middle to side arrowstick
#5	Single half to half (ECE R65)	#15	One - One Octa	#25	Arrowstick combination
#6	Double half to half (ECE R65)	#16	Center - out single flash	#26	Left Steady - Right Single
#7	Quad half to half (ECE R65)	#17	CW Rotation	#27	Right Steady - Left Single
#8	Octa half to half	#18	CCW Rotation	#28	Steady on
#9	Single - Slow (CAP168/ICAO)	#19	CW Constant flash		
#10	Breath flash	#20	CCW Constant flash		

Controller Functions

	ON/OFF (Power)	←	Left arrowstick	COLOR	Color Option
M or FLASH On/Off	ON/OFF (FLASH)	↔	Middle to side arrowstick	L/A or Left Alley	Left alley
	Previous pattern	⇒	Right arrowstick	R/A or Right Alley	Right alley
	Next pattern	CRUISE	Steady on	F/S or Front Spot	Front spot
DIM	Day/Night mode	F/R	Front/Rear	R/S or Rear Spot	Rear spot

PART #

LENGTH

WIDTH

COLOUR EMITTING

VOLTAGE

LENS MATERIAL

BASE MATERIAL

OPERATING TEMP.

26010-47

47"

7.9"

Amber/White

12-24Vdc

Polycarbonate

Aluminum

-30°C - +60°C